

gHAWK: Local and Global Structure Encoding for Scalable Training of Graph Neural Networks on Knowledge Graphs

Humera Sabir*
University of Texas at Arlington
humera.sabir@uta.edu

Fatima Farooq*
University of Texas at Arlington
fatima.farooq@uta.edu

Ashraf Aboulnaga
University of Texas at Arlington
ashraf.aboulnaga@uta.edu

ABSTRACT

Knowledge Graphs (KGs) are a rich source of structured, heterogeneous data, powering a wide range of applications. A common approach to leverage this data is to train a graph neural network (GNN) on the KG. However, existing message-passing GNNs struggle to scale to large KGs because they rely on the iterative message passing process to learn the graph structure, which is inefficient, especially under mini-batch training, where a node sees only a partial view of its neighborhood. In this paper, we address this problem and present gHAWK, a novel and scalable GNN training framework for large KGs. The key idea is to precompute structural features for each node that capture its local and global structure before GNN training even begins. Specifically, gHAWK introduces a preprocessing step that computes: (a) Bloom filters to compactly encode local neighborhood structure, and (b) TransE embeddings to represent each node’s global position in the graph. These features are then fused with any domain-specific features (e.g., text embeddings), producing a node feature vector that can be incorporated into any GNN technique. By augmenting message-passing training with structural priors, gHAWK significantly reduces memory usage, accelerates convergence, and improves model accuracy. Extensive experiments on large datasets from the Open Graph Benchmark (OGB) demonstrate that gHAWK achieves state-of-the-art accuracy and lower training time on both node property prediction and link prediction tasks, topping the OGB leaderboard for three graphs.

1 INTRODUCTION

Knowledge graphs (KGs) are structured representations of real-world entities and the relations among them. They are widely used in various applications, including question-answering [19, 26, 31], recommendation systems [17, 23], and information retrieval [10, 50]. A KG is a *heterogeneous graph*, meaning that it has multiple node and edge types. Each node in a KG represents an entity and belongs to an *entity type*. Nodes can also have type-specific attributes (e.g., a *Person* node may have a *name* attribute). Edges are directed and represent a specific type of relation between entities. An edge connects a source node (the *head entity*) to a destination node (the *tail entity*) and is labeled with a *relation type* (e.g., a *HasAuthor* edge linking a *Paper* node to a *Person* node). Thus, a KG can be represented as a set of (*head, relation, tail*) triples, and modern KGs often contain millions of such triples and hundreds of relation types [20].

To fully leverage the rich, structured information in a KG, a first step in many applications is training a machine learning model on the graph. Graph neural networks (GNNs) have emerged as a powerful class of models, with demonstrated success in diverse graph-based tasks. Originally designed for homogeneous graphs

(single node and edge type), GNNs have been extended to heterogeneous graphs [8, 22, 37, 45]. GNNs learn latent vector *representations* of nodes, also known as *embeddings* of the nodes in a vector space, directly leveraging the graph topology as a computation graph to update the node embeddings during training, as described next.

At each layer of the neural network, a node gathers *messages* from its neighbors and updates its embeddings by aggregating these messages. This process is repeated iteratively and is referred to as *message passing* [43]. During message passing, each node progressively integrates information from its immediate and multi-hop neighborhoods into the node representation. In a KG, the integrated information comprises node-level features, such as entity types and attribute representations, and edge-level features, such as relation types, which encode the semantic connections between nodes. By capturing this heterogeneous structural and semantic information, GNNs can substantially improve predictive accuracy on downstream KG tasks [24].

While GNNs have demonstrated remarkable predictive accuracy, ***training GNNs on large-scale heterogeneous KGs poses serious scalability challenges***. These challenges have attracted significant attention in the database community [1, 25, 48, 56, 57]. In this paper, we present a scalable and efficient framework for training GNNs on KGs that is motivated by the following key observation: The parameters of a GNN must ultimately encode information about the graph’s structure. Consequently, the GNN must *learn* the structure of the KG during training. In message-passing GNNs, this structural information is acquired only through iterative neighborhood aggregation, where each node can only access information from its immediate neighbors in each message-passing iteration. ***As a result, nodes accumulate structural information only gradually over multiple iterative rounds of message passing and aggregation, which is inherently lossy and inefficient.***

Three factors exacerbate this inefficiency for KGs compared to homogeneous graphs. First, KGs exhibit substantially higher structural diversity: many pairs of entity types may be connected by multiple distinct relation types, and real-world KGs often include hundreds of such relations [47]. Capturing this rich structural and semantic heterogeneity introduces additional complexity during training and further reduces efficiency. Second, GNNs designed for KGs (which we call *relation-aware*) maintain separate parameter sets for each relation type [13, 37, 45]. Consequently, these models must learn far more parameters than GNNs for homogeneous graphs, increasing computational cost and slowing convergence. Third, it is typically not feasible to train a GNN on a KG in *full-batch* mode, where all nodes and their full neighborhoods are processed in each training epoch, since the memory requirement would be prohibitively high. Instead, GNNs are typically trained using *mini-batch* training, in which each node’s neighborhood is *sampled* and

*Equal contribution.

message passing is performed only on the sampled subgraph [2, 11, 29, 34]. This sampling inevitably discards valuable neighborhood information, leading to reduced accuracy and slower convergence.

We argue that scalable GNN training on large KGs fundamentally requires *precomputed structural priors* so that mini-batch message passing starts from an information-rich representation of graph structure rather than attempting to reconstruct this structure from neighborhood samples. Our high-level insight is to *shift the complexity of capturing the KG structure from the message-passing stage to a lightweight preprocessing step*. We design a GNN framework that preprocesses the graph before GNN training to compute features for each node that encode the graph structure from the node’s perspective. A key design decision we made is to compute two separate and complementary structural feature vectors for each node: one representing the *local* neighborhood structure and the other representing the *global* graph structure. These vectors are then *fused* with each other and with any domain-specific feature vectors in the KG nodes, producing a single feature vector per node that succinctly and accurately captures the node’s structural context throughout GNN training. We call our framework *gHAWK* (for *Hybrid Aggregation of local and global structure for Web-scale KGs*). *gHAWK* can be used with any GNN architecture (the GNN *backbone*) and for any downstream graph prediction task.

To represent each node’s local structure, we use a *Bloom filter* [4] to encode the node’s 1-hop neighbors. The Bloom filter encodes neighbors reachable via both incoming and outgoing edges (i.e., triples in which the node is either the tail or the head). The Bloom filter hashes these neighbors into a fixed-length bit vector, providing an accurate and succinct approximation of each node’s 1-hop neighborhood, which helps to recover information lost by sampling.

To represent each node’s position in the *global* graph structure, *gHAWK* uses the node’s *TransE* embedding vector [6]. *TransE* belongs to a class of methods, known as *knowledge graph embedding (KGE)* models, which learn embeddings of the nodes and edges of a KG in a continuous vector space not by training a GNN, but rather by optimizing a scoring function that reflects the plausibility of triples [15, 49]. *TransE* embeddings can be computed efficiently even for large KGs and have proven effective at capturing KG structure and supporting accurate prediction [2].

TransE embeddings offer several advantages during training, beyond simply summarizing the graph’s global structure. First, the relations connecting entities in a KG represent semantic information about these entities. For example, the relations in which a *Person* node participates differ fundamentally from the ones associated with a *City* node. *TransE* embeddings capture these relational semantics, which we refer to as the *semantic context* of a node. Second, message passing in GNNs conveys information about distant neighbor nodes only through messages that have undergone several rounds of aggregation, reducing the quality of this information, a problem known as *over-squashing* [9]. *TransE* mitigates this by injecting global structural information into each node. Finally, because the distribution of relation types in many KGs is highly skewed [30], some relation types are rarely observed during training. *TransE* provides information on these infrequent relations.

After preprocessing, each KG node has two structural feature vectors: the Bloom filter representing its 1-hop neighborhood and the *TransE* embedding representing its global structural position.

Many KGs also include domain-specific feature vectors, for example, those derived from node attribute values or from text embeddings obtained from pre-trained language models such as RoBERTa [27]. *gHAWK* fuses all these vectors into a single feature vector per node, using a learned model to combine the information from all vectors effectively, adaptively weighting structural and domain-specific priors. The fused feature vector can often be made *smaller* than the original domain-specific feature vector without loss of accuracy and with improved training time.

We evaluate *gHAWK* on two widely studied KG prediction tasks: (1) *node property prediction* (also called *node classification*), in which the goal is to assign labels or categories to entities, and (2) *link prediction*, in which the goal is to infer missing relations between existing entities. For link prediction, the training data must include *negative samples*, i.e., triples known to *not* exist in the KG. It is well established that using hard (i.e., non-obvious) negative samples yields better models [41], and one of the added benefits of *gHAWK* is that it can leverage the *TransE* model trained during preprocessing to effectively generate hard negative samples.

Our evaluation uses standard datasets from the Open Graph Benchmark (OGB) [20, 21], focusing on large and/or highly heterogeneous KGs (MAG, MAG240M, WikiKG2, and FB15k-237). We use mini-batch training in our experiments and observe that the structural features computed by *gHAWK* restore the accuracy lost due to sampling during mini-batch formation. Across all benchmarks, *gHAWK* achieves superior performance, simultaneously improving accuracy and reducing training time. In addition, at the time of writing, *gHAWK* **ranks first on the OGB leaderboard for two large node property prediction benchmarks and one large link prediction benchmark**. To the best of our knowledge, no other technique ranks first on multiple OGB leaderboards.

In summary, this paper makes the following contributions:

- **Hybrid local and global structure encoding.** We propose the idea of pre-computing node features that represent KG structure, and separately encoding local and global structure.
- **Local structure encoding via Bloom filters.** We encode each node’s local multi-relational neighborhood in a fixed-size Bloom filter, giving the GNN a compressed view of all 1-hop neighbors without storing full adjacency lists, thereby compensating for the information lost by sampling.
- **Global structure encoding via TransE.** We use *TransE* embedding vectors to encode global structure and capture the semantic context of the nodes.
- **Feature vector fusion.** We combine the local and global structure encoding vectors, along with domain-specific feature vectors, into a single, succinct feature vector for each node.
- **Hard negative sampling.** We use the *TransE* model to generate effective hard negative samples for link prediction models.
- **Extensive evaluation.** *gHAWK* outperforms state of the art on multiple benchmarks and ranks first on three OGB leaderboards.

The complete *gHAWK* pipeline is depicted in Figure 1, and its components are described in the rest of the paper. Section 2 reviews relevant background. Sections 3 and 4 describe *gHAWK*. Section 5 analyzes time and space complexity. Section 6 presents experiments. Section 7 reviews related work, and Section 8 concludes.




Figure 1: gHAWK pipeline. (a) Input knowledge graph. (b) Node feature computation: in a preprocessing step, gHAWK constructs a Bloom filter encoding the 1-hop neighbors of each node and trains a TransE embedding model to capture the global graph structure. (c) Feature fusion: for every node, the Bloom filter, TransE embedding, and any domain-specific feature vector are fused in the preprocessing step via an MLP, creating a dense fused feature vector. (d) Mini-batch message passing: the fused vectors initialize a message-passing GNN that is trained on sampled mini-batch subgraphs of the knowledge graph. (e) Task-specific heads: the resulting node embeddings are fed into separate heads for node property prediction (where embeddings directly predict node labels via a supervised loss) and for link prediction (where node embeddings are combined with relation embeddings in a decoder to score candidate triples).

2 BACKGROUND

2.1 Knowledge Graphs

We formally define a knowledge graph as $G = (\mathcal{E}, \mathcal{R}, \mathcal{T})$, where $\mathcal{E}$ is the set of entities (nodes), $\mathcal{R}$ is the set of relation types (edge labels), and $\mathcal{T}$ is a set of factual triples (h, r, t) , with $h, t \in \mathcal{E}$ and $r \in \mathcal{R}$. Each triple asserts that a head entity h is connected to a tail entity t via relation r .

2.2 Bloom Filters for Set Representation

We use Bloom filters [4] to represent the 1-hop neighborhood of each node. Bloom filters are probabilistic data structures designed for memory-efficient set membership queries. A Bloom filter consists of an m -bit array B and uses k independent hash functions $h_i(\cdot)$. Given a set $S = \{s_1, s_2, \dots, s_n\}$, each element $s \in S$ is represented in B by setting the bits at positions $h_i(s) \bmod m$ to 1, for $i = 1, \dots, k$. To test whether an element x belongs to S , we check whether all k bits at positions $h_i(x) \bmod m$ of B are set to 1. Bloom filters guarantee no false negatives (any present element is always reported as present), but may produce false positives with probability

$$\varepsilon = \left(1 - e^{-kn/m}\right)^k,$$

where n is the number of inserted elements. Parameters m and k are chosen to achieve an acceptable false-positive rate (e.g., $\varepsilon < 0.01$). Due to their low memory footprint and constant-time query performance, Bloom filters are widely used in data-intensive applications, including databases, storage systems, and web indexing.

2.3 Knowledge Graph Embeddings

KGE methods embed the entities and relations of a KG into a continuous vector space by optimizing a scoring function defined over that space. This scoring function measures the plausibility of triples and is trained so that triples present in the KG receive higher scores than corrupted (i.e., non-existent) triples. The resulting embeddings aim to capture both the structural and semantic properties of the KG while supporting downstream predictive tasks.

A widely used KGE method is TransE [6], which we adopt to encode the global structure of a KG. TransE models each relation as a vector translation from the head to the tail entity. Given a triple (h, r, t) , TransE learns embeddings $\mathbf{h}, \mathbf{r}, \mathbf{t} \in \mathbb{R}^d$ such that $\mathbf{h} + \mathbf{r} \approx \mathbf{t}$. This is achieved by optimizing the scoring function

$$f(h, r, t) = -\|\mathbf{h} + \mathbf{r} - \mathbf{t}\|_p, \quad (1)$$

where $p \in \{1, 2\}$. Section 3.2 presents the details of training TransE so that true triples receive higher scores than corrupted triples.

Although TransE is simple and scalable, it cannot model one-to-many, many-to-many, or symmetric relations, motivating extensions that enforce other objectives and use other scoring functions [49]. RotatE [41], for example, represents each relation as a rotation in the complex plane, enabling it to capture diverse relation patterns such as symmetry, antisymmetry, inversion, and composition. RotatE enforces $\mathbf{t} \approx \mathbf{h} \circ e^{i\mathbf{r}}$, where $e^{i\mathbf{r}}$ is the element-wise complex exponential of the relation vector $\mathbf{r}$ and $\circ$ denotes element-wise complex multiplication [41]. Its scoring function is

$$f(h, r, t) = -\|\mathbf{h} \circ \mathbf{r} - \mathbf{t}\|, \quad (2)$$

where $\mathbf{h}, \mathbf{r}, \mathbf{t}$ are complex-valued vectors.

DistMult [51] (bilinear dot product) uses the scoring function:

$$f(h, r, t) = \mathbf{h}^\top \text{diag}(\mathbf{r}) \mathbf{t}. \quad (3)$$

Here, each relation r is represented by a vector whose entries scale the interaction between components of h and t . DistMult is symmetric in h and t (since $\mathbf{h}^\top \text{diag}(\mathbf{r}) \mathbf{t} = \mathbf{t}^\top \text{diag}(\mathbf{r}) \mathbf{h}$), which makes it well-suited for symmetric relations.

gHAWK uses TransE to encode global structure because it effectively captures the semantic context of nodes and is highly efficient to compute and parallelize [25] (we elaborate on this point in Section 3.2). Furthermore, empirical studies have shown that TransE outperforms more complex KGE models [42]. In addition, TransE produces real-valued embeddings, which integrate seamlessly into a GNN training pipeline. In contrast, models such as RotatE produce complex-valued vectors, requiring an additional conversion step before they can be used within training pipelines.

gHAWK uses other KGE models, such as RotatE and DistMult, as the GNN scoring head for link prediction (Section 4.2).

2.4 Graph Neural Networks

GNNs learn node embeddings by *message passing*: each layer in the network aggregates and transforms information from a node’s neighbors, then feeds the result to the next layer. While GNNs for homogeneous graphs treat all edges identically, KGs contain multiple edge types, motivating the use of *relation-aware GNNs* such as R-GCN [37], where aggregation explicitly accounts for relation types. Given a KG $G = (\mathcal{E}, \mathcal{R}, \mathcal{T})$, a relation-aware GNN layer updates the embedding of node i at layer $(\ell + 1)$ as

$$\mathbf{h}_i^{(\ell+1)} = \sigma \left(W_0^{(\ell)} \mathbf{h}_i^{(\ell)} + \sum_{r \in \mathcal{R}} \sum_{j \in \mathcal{N}_r(i)} \frac{1}{|\mathcal{N}_r(i)|} W_r^{(\ell)} \mathbf{h}_j^{(\ell)} \right), \quad (4)$$

where $\mathbf{h}_i^{(\ell)} \in \mathbb{R}^d$ is the embedding of node i at layer ℓ , $W_0^{(\ell)}$ and $W_r^{(\ell)}$ are trainable parameter matrices for self-loop and relations, $\mathcal{N}_r(i)$ is the set of neighbors of node i connected via relation r , and $\sigma(\cdot)$ is a nonlinear activation function (e.g., ReLU or sigmoid). **A notable feature of gHAWK is that, in addition to working with relation-aware backbones, it can also inject relation awareness into a relation-agnostic GNN backbone (Section 4.1).**

2.5 Predictive Tasks on GNNs

In this paper, we focus on two predictive tasks on KGs: node property prediction and link prediction, defined formally as follows.

2.5.1 Node Property Prediction. In node property prediction, which is essentially a node classification task, each entity may have an associated label (or attribute value), and the aim is to predict the labels of unlabeled entities by exploiting the graph’s structure and known labels. Let $\mathcal{E}_L \subset \mathcal{E}$ be the set of labeled nodes with ground-truth labels $Y = \{y_e \mid e \in \mathcal{E}_L\}$. The goal is to learn a function $g_\theta : \mathbf{h}_e \rightarrow \hat{y}_e$, trained to generalize from $\mathcal{E}_L$ to the unlabeled nodes $\mathcal{E}_U = \mathcal{E} \setminus \mathcal{E}_L$. Training g_θ by learning the parameters θ involves minimizing a classification loss over the labeled nodes in $\mathcal{E}_L$ to fit their ground-truth labels.

2.5.2 Link Prediction. Link prediction (also called knowledge graph completion) seeks to infer missing or unobserved links in

the graph. Given an incomplete KG, the goal is to identify which potential triples (h, r, t) are likely to be true. Formally, this involves learning a *scoring function* (also referred to as a *decoder* or *scoring head*) $f_\theta(h, r, t)$, where θ is a learnable set of parameters, that assigns a high score to a triple if it corresponds to a true fact in the KG and a low score otherwise. During inference, all candidate triples can be ranked by $f_\theta(h, r, t)$, and the highest-scoring ones are predicted as new links. We optimize f_θ in a contrastive fashion: for every positive triple $(h, r, t) \in \mathcal{T}$ we generate a set of *negative* triples $\mathcal{T}^-$ by randomly corrupting the head or tail, (h', r, t) or (h, r, t') . The scoring function is optimized so that positive triples obtain higher scores than their corresponding negatives, typically by imposing a margin or softmax-based separation. Intuitively, f_θ learns the compatibility of entity and relation embeddings so that true triples stand out against randomly generated ones.

3 STRUCTURE ENCODING

The first stage of the gHAWK pipeline is a preprocessing step that (i) constructs Bloom filters for neighborhood encoding, (ii) trains a TransE model for global structure encoding, and (iii) fuses the various node feature vectors into a unified representation. After this stage, the GNN is trained using standard message passing. This section describes preprocessing, and Section 4 discusses GNN training.

3.1 Bloom Filters For Neighborhood Encoding

Rationale. A KG node can learn about its 1-hop neighbors in a single round of message passing if full-batch training is used, since the node receives and aggregates messages from *all* its neighbors. However, full-batch training is typically infeasible for large KGs due to memory constraints, so training randomly samples the neighbors of a node, providing only a partial view of the neighborhood.

One way to mitigate this loss of neighborhood information is to store the set of neighbors as a feature in each node. We choose to represent this set using a Bloom filter since Bloom filters are fixed-length, tunable, accurate, easy to compute, and easy to query. This allows each node to retain a lightweight approximate summary of its full neighborhood, independent of sampling during mini-batch formation and without explicitly storing adjacency lists. The Bloom filter provides a noisy structural prior that the downstream GNN model must still interpret, but we show that it is effective at mitigating information loss due to sampling and improving training accuracy.

Algorithm 1: BUILD BLOOM FILTERS

Input : $\mathcal{T}$ (triple list), m (number of bits), k hash functions
Output : $\{B[i]\}_{i \in \mathcal{E}}$ (Bloom filters for all nodes)
foreach $i \in \mathcal{E}$ **do**
 initialize $B[i] \leftarrow \mathbf{0}_m$
foreach $(h, r, t) \in \mathcal{T}$ **do**
 $B[h].\text{insert}("r_t")$;
 $B[t].\text{insert}("r_h")$;
return $\{B[i]\}$

Bloom Filter Construction. We assign each node $i \in \mathcal{E}$ in the KG an m -bit Bloom filter that encodes its 1-hop neighborhood: $B[i] \in \{0, 1\}^m$. The Bloom filters for all nodes in the KG are denoted

by the set $\{B[i]\}_{i \in \mathcal{E}}$, indexed by node ID i . This set can be constructed in a single pass over the triples, as shown in Algorithm 1.

To ensure that $B[i]$ accurately reflects the 1-hop neighborhood of node i , it must include i 's neighbors that are reachable via both outgoing edges, where i is the head in a triple (i, r, t) , and incoming edges, where i is the tail in a triple (h, r, i) . Moreover, it is important to record not only the neighbor's node ID, but also the relation type connecting the two nodes. For outgoing edges, we encode the neighbor and the connecting relation using the string " r_t ", and for incoming edges, we use " r_h ". Here, r denotes the relation identifier, which represents the relation type, and t/h denotes the node ID of the neighbor, which uniquely identifies the node in the graph.

Algorithm 1 processes the KG not node-by-node, but triple-by-triple. For every triple $(h, r, t) \in \mathcal{T}$, the algorithm insert two strings into two Bloom filters: (1) The string " r_t " into $B[h]$. (2) The string " r_h " into $B[t]$. Inserting a string into a Bloom filter follows the standard procedure: The string is hashed with k independent hash functions to k bit positions in the m -bit Bloom filter, and all those bits are set to 1. After processing all triples, $B[i]$ contains a compact approximate encoding of the relations and neighbors of node i without explicitly storing any neighbors [38] (see Figure 2 for an example).

Parameter Choice. To ensure that the Bloom filter operates efficiently at scale, we carefully select its configuration parameters based on the properties of the KG. The main dataset-dependent parameter is the number of elements to be inserted into each Bloom filter, denoted as n . A naive choice for n is the maximum fan-out (out-degree plus in-degree) across all KG nodes. However, the fan-out distribution in many KGs is highly skewed, with a handful of outliers with very high fan-out. For example, in the MAG240M publication KG [20], which we use in our experiments, a few papers have extremely large citation count or unusually many authors. To avoid these outliers, we compute the 95th percentile of the node out-degrees and in-degrees. The sum of these two values serves as our estimate for n , providing a stable and representative estimate of the typical neighborhood size while preventing a few anomalous nodes from forcing an unnecessarily large Bloom filter.

Given n and a desired false-positive rate ϵ (e.g., 1%), it is possible to compute the Bloom filter parameters using standard formulas [4]. The required bit length m of the filter is calculated as

$$m = -\frac{n \cdot \ln(\epsilon)}{(\ln 2)^2},$$

and the optimal number of hash functions k is given by

$$k = \frac{m}{n} \cdot \ln 2.$$

These choices ensure a balance between space efficiency and accuracy. Once m is determined, the number of bytes required per Bloom filter can be computed as $\lceil \frac{m}{8} \rceil$. This byte count directly determines the memory footprint for storing the Bloom filters. When $m \leq 1024$, we store each Bloom filter as a `uint32` array. For $m > 1024$ we compress via run-length encoding and store the Bloom filters in a single memory-mapped file on-disk, ensuring that only the Bloom filters needed are paged into memory.




Figure 2: Local and global view in gHAWK. Left: a target node n_1 and its 1-hop neighbors $\{n_2, \dots, n_6\}$ with relation types $\{r_1, r_2, r_3\}$. The neighbors are hashed k times into a fixed-length m -bit Bloom filter, producing a signature that preserves the neighborhood. Right: the same node shown as a head node h in a two-dimensional projection of the TransE embedding space. The relation vector r is a translation from h to tail t , illustrating $h + r \approx t$. The node embedding h encodes the position of the node within the graph global structure and captures the node's semantic context.

3.2 TransE For Global Structure Encoding

gHAWK uses TransE to provide each node with a representation of its global position in the KG. As part of preprocessing, we train a TransE model on all triples in the KG following the standard procedure of [6]. For each triple (h, r, t) , we generate one negative triple (h', r, t') (i.e., a triple not in the KG) by corrupting either the head or the tail, replacing the corrupted entity with a uniformly sampled entity. Training minimizes the margin-based loss

$$\max(0, \gamma + f(h', r, t') - f(h, r, t)),$$

where $f(\cdot)$ is the TransE scoring function defined in Equation 1 and γ is the margin (we use $\gamma = 1.0$). This loss function encourages the model to assign strictly higher scores to true triples than to their corrupted counterparts, yielding entity embeddings that capture global structural regularities of the KG.

TransE provides embedding vectors for every node in the KG and for every relation type. The node embeddings effectively capture global relational structure at low computational cost, improving the effectiveness of message passing and its convergence. By providing each node with a global structural signal, these embeddings also help integrate information from distant neighbors during training, thereby mitigating over-squashing [9]. In addition, TransE node embeddings can inject semantic context into GNN architectures that do not explicitly capture it (i.e., relation-agnostic GNNs), and they provide information about infrequent relations that are under-represented during training.

For the purpose of global structure encoding in gHAWK, TransE is more suitable than more complex KGE methods such as RotatE or DistMult. Global structure encoding requires a KGE method where node embeddings alone reflect the global structure of the graph and can be interpreted without requiring the relation embeddings. The KGE method should also be scalable and efficient. TransE satisfies these requirements. Its training objective organizes entities in a Euclidean space where distances and directions correspond to relational structure: a relation corresponds to a translation, and

composed relations correspond to vector addition. As a result, the node embeddings alone encode a coherent notion of proximity and position in the graph, even without the relation embeddings. At a high level, the node embeddings can be viewed as a global coordinate system based on graph structure. In addition, TransE is scalable, efficient, and parallelizable [25].

In contrast, DistMult and RotatE are optimized for scoring triples in link prediction, not for encoding graph structure. DistMult is inherently symmetric and lacks the directional modeling of TransE, so it does not induce a structurally meaningful placement of entities in the embedding space. RotatE models relations as complex rotations, and scoring a triple depends primarily on interactions with the relation embeddings. Without relation embeddings, the entity embeddings do not encode graph structure in a meaningful way. Thus, while DistMult and RotatE excel at link prediction, TransE is far better for global structure encoding in gHAWK.

3.3 Fusion of Node Features

At the end of the gHAWK preprocessing step, each node in the graph has two feature vectors representing its structure: (i) a Bloom filter representing the local structure and (ii) a TransE embedding vector encoding its global position in the KG. Many KGs additionally provide domain-specific node features derived from node attributes. For example, in the MAG240M publication KG used in our experiments, each node representing a published article has as a feature the RoBERTa embedding of its title and abstract [20]. As another example, in KGs constructed from relational databases [35], each node corresponds to a table row and the attribute values of this row are summarized in a feature vector. When such domain-specific features are available, they must be incorporated into GNN training alongside the Bloom filters and TransE embeddings.

A key design question in gHAWK is how to combine these heterogeneous feature vectors into a representation suitable for GNNs. A naive solution is to concatenate the three vectors directly. However, this performs poorly because the vectors lie in fundamentally different spaces: Bloom filters inhabit a sparse binary Hamming space, TransE embeddings reside in a continuous translation-based Euclidean space, and domain-specific features occupy an application-defined semantic space (e.g., a RoBERTa embedding space). Moreover, the fused representation must ultimately live in the GNN’s latent space. These spaces differ in dimensionality, scale, distribution, and semantics, making raw concatenation ineffective.

To address this challenge, gHAWK employs a *learned model for feature fusion*. For each node i , gHAWK assumes three input feature vectors: a Bloom filter $B[i] \in \{0, 1\}^m$, a TransE embedding $\mathbf{e}_i \in \mathbb{R}^{d_E}$, and a domain-specific feature vector $\mathbf{x}_i \in \mathbb{R}^{d_X}$. These vectors are *frozen* and never updated after they are computed. The feature fusion model learns to weight and combine these vectors across nodes and tasks, rather than treating them as static inputs. Fusion proceeds in two steps using lightweight *multi-layer perceptrons* (MLPs).

First, each input vector is independently projected into a common d -dimensional latent space via three two-layer MLPs with ReLU activation and dropout, g_E , g_B , and g_X :

$$\mathbf{t}_i = g_E(\mathbf{e}_i) \in \mathbb{R}^d, \quad \mathbf{b}_i = g_B(B[i]) \in \mathbb{R}^d, \quad \mathbf{x}'_i = g_X(\mathbf{x}_i) \in \mathbb{R}^d.$$




Figure 3: Feature-fusion module in gHAWK. For each node i , the frozen Bloom filter $B[i]$, TransE embedding $\mathbf{e}_i$, and optional domain-specific feature vector $\mathbf{x}_i$ are passed through dedicated two-layer MLPs g_B , g_E , and g_X into a common d -dimensional space, concatenated into $\mathbf{z}_i$, and mapped by $\mathbf{W}_{\text{in}}$ and a nonlinear activation function $\phi(\cdot)$ into the initial GNN input embedding $\mathbf{h}_i^{(0)}$. All parameters in the projection MLPs and fusion layer are learnable and are updated jointly with the GNN and decoder during training.

These projections denoise, rescale, and harmonize the heterogeneous inputs, ensuring that the resulting vectors are numerically comparable despite originating from distinct modalities.

Note that domain-specific features are optional and not present in many KGs. For example, none of the KGs used in our link prediction experiments have such features. When these features are absent, g_X is omitted and $\mathbf{x}'_i$ is excluded from subsequent computations.

We set the projection size d equal to the dimensionality of the TransE embeddings (i.e., $d = d_E$), which empirically provides a balanced capacity across feature types. Experiments with larger or smaller d , or with separate projection sizes for each feature type, did not improve accuracy and often increased computational cost.

Second, the projected vectors are concatenated and mapped into the GNN’s input space:

$$\mathbf{z}_i = [\mathbf{t}_i \parallel \mathbf{b}_i \parallel \mathbf{x}'_i] \in \mathbb{R}^{d_F}, \quad \mathbf{h}_i^{(0)} = \phi(\mathbf{W}_{\text{in}}\mathbf{z}_i + \mathbf{b}_{\text{in}}),$$

where $d_F = 3d$ (or $2d$ when domain-specific features are absent), $\mathbf{W}_{\text{in}} \in \mathbb{R}^{h \times d_F}$ and $\mathbf{b}_{\text{in}}$ are learnable parameters, $\mathbf{h}_i^{(0)}$ is the initial GNN node representation of dimension h , and $\phi(\cdot)$ is a nonlinear activation function (ReLU in our implementation). Layer normalization can be applied to $\mathbf{h}_i^{(0)}$ to improve optimization stability [3].

The two steps of the fusion process together define a *three-layer neural network* that maps the frozen Bloom, TransE, and domain-specific vectors into the GNN’s latent space. This fusion pipeline is summarized in Figure 3, which shows the three projection MLPs feeding into a shared fusion layer that produces the initial GNN node embedding.

Crucially, the projection MLPs g_E, g_B, g_X and the weights of the fusion layer, W_{in} and b_{in} , are *not* trained by a separate auxiliary objective. They are optimized *end-to-end* together with the GNN and decoder weights using the downstream task loss (Section 4.2). At the end of the gHAWK preprocessing step, we perform one pass over the whole training data and train only the fusion module, without modifying the GNN or decoder weights. That is, gradients from the task loss flow through the decoder and GNN layers back into g_E, g_B, g_X, W_{in} , and b_{in} . After preprocessing, we move to GNN training and we train the GNN and decoder weights. We continue to train the fusion module during GNN training, but use a lower learning rate than the one used during preprocessing. Throughout this process, the underlying Bloom filters, TransE embeddings, and domain-specific feature vectors remain frozen.

This setup allows gHAWK to learn the relative importance of the different feature vectors based solely on task supervision. For example, if a node has a high degree (i.e., many neighbors), the Bloom filter will consist of almost all 1’s and will therefore carry limited additional information. In this case, the fusion model will learn to rely more heavily on the TransE or domain-specific features. Conversely, for low-degree or structurally distinctive nodes, the Bloom filter becomes highly informative, and the corresponding projection g_B contributes more strongly. The learned fusion thus adapts to both the *geometry* of each feature space and the *local graph context*, rather than imposing a fixed, hand-crafted combination.

4 GNN TRAINING

4.1 gHAWK-Enhanced GNN Architectures

gHAWK is compatible with any GNN architecture. With gHAWK, layer 0 of the GNN (i.e., the node representation) consists of the standard trainable GNN parameter vector augmented with the fused feature vector produced by gHAWK (Figure 3). This combined representation is propagated during message passing, thereby injecting structure awareness directly into the GNN’s training process. The underlying GNN trainable parameters are updated exactly as in the original architecture. The gHAWK feature vector itself is not updated directly; instead, the MLP that generates it is trained as described in Section 3.3. Next, we discuss how gHAWK enhances three categories of GNNs, listed from least to most scalable: (1) *relation-aware* GNNs, (2) *relation-agnostic* GNNs, and (3) *decoder-only* GNNs.

Relation-aware GNNs such as R-GCN [37] maintain a distinct weight matrix for each relation type and learn all these weights during training. This explicit modeling of relations enables these GNNs to capture relational semantics with high fidelity, but at a substantial cost: the number of learned weight matrices grows linearly with the number of KG relations. Consequently, relation-aware GNNs scale poorly as the number of relations grows. gHAWK mitigates this problem by improving the training starting point.

Relation-agnostic GNNs such as GraphSAGE [18] share GNN parameters across all relations. That is, they ignore relation types and treat the graph as homogeneous. This design is far more memory-efficient, but often lower accuracy since it discards valuable relation-type information. Since gHAWK injects information about the relational structure of the KG into the node representation, it is particularly valuable for improving relation-agnostic GNNs. For large heterogeneous KGs, where relation-aware models become

impractical due to memory overhead, a relation-agnostic backbone enhanced with gHAWK offers an attractive alternative. Moreover, gHAWK can introduce relational semantics in the decoding stage as well (details in the next section). Notably, our experiments show that relation-agnostic GNNs augmented with gHAWK frequently outperform relation-aware models on large heterogeneous graphs.

Every GNN ultimately employs a final, learned decoder block to map embeddings to task-specific outputs. This decoder does not correspond to any specific node and does not participate in message passing. It is possible to train a GNN consisting solely of this decoder, without any message passing. Such decoder-only GNNs are extremely scalable because they have few parameters and a simple structure, though they are typically less accurate than message-passing GNNs. gHAWK can improve the accuracy of decoder-only GNNs by supplying the structural and relational information that message passing would otherwise provide.

Standard message-passing GNNs use k layers to aggregate information from the k -hop neighborhood, with $k = 2$ being common. That is, layer 0 encodes the node’s own features, layer 1 aggregates information from 1-hop neighbors, and layer 2 from 2-hop neighbors. With gHAWK, it is often possible to achieve high accuracy with $k = 1$, i.e., with message passing only from the immediate (1-hop) neighbors. In some cases, a decoder-only GNN, which can be viewed as zero-hop message passing, is sufficient.

gHAWK ultimately provides fine-grained control over (a) relation awareness, (b) message-passing depth, and (c) the fraction of nodes sampled for mini-batch construction. This flexibility enables practitioners to tailor GNN training to available memory, compute resources, dataset characteristics, and application requirements. In our experiments, we found that relation-agnostic backbones combined with gHAWK’s features and relation-aware decoders perform best for most KGs, while decoder-only models with gHAWK features offer the best scalability-accuracy tradeoff at extreme scale.

4.2 Task-Specific Decoders

The node embeddings $h_i^{(L)}$ produced by the GNN can be used for a variety of prediction tasks. A final neural network block maps these embeddings to task-specific outputs by computing a *score* using a *task-specific scoring function*. This final block is commonly referred to as the *decoder* or *scoring head*. The decoder parameters are trained jointly with the rest of the GNN.

In this paper, we focus on two tasks: node property prediction and link prediction. This section presents the decoders for these tasks. As mentioned in the previous section, a decoder can be trained as a stand-alone GNN without the message-passing layers. This is a highly scalable but potentially less accurate option for large KGs.

4.2.1 Node Property Prediction. In node property prediction, the decoder (also known as a *classification head*) predicts a class label from the final node embedding $h_i^{(L)} \in \mathbb{R}^d$. gHAWK uses a two-layer MLP for this decoder:

$$\hat{y}_i = \text{softmax}\left(W_2 \phi(W_1 h_i^{(L)} + b_1) + b_2\right), \quad (5)$$

where $W_1 \in \mathbb{R}^{m \times d}$ projects $h_i^{(L)}$ to an m -dimensional hidden layer, $W_2 \in \mathbb{R}^{C \times m}$ maps to C class logits, b_1 and b_2 are biases, and $\phi(\cdot)$ is

a pointwise nonlinearity (we use ReLU). The training objective for this head is a mini-batch cross-entropy loss, described in Section 4.3.

4.2.2 Link Prediction. The goal of a link prediction decoder, also known as a *triple scoring head*, is to estimate the plausibility of a candidate triple (h, r, t) , where h and t are head and tail nodes and r is a relation type.

Let $\mathbf{h}_h^{(L)}, \mathbf{h}_t^{(L)} \in \mathbb{R}^d$ denote the final embeddings of the head and tail nodes produced by gHAWK. For the decoder-only variant, these are the fused gHAWK features without message passing. The decoder maintains a trainable embedding $\mathbf{r}$ for every relation r and computes a scalar score

$$f(h, r, t) \in \mathbb{R}$$

such that higher values indicate a more plausible triple. The embedding $\mathbf{r}$ can be initialized randomly or using the TransE embeddings computed by gHAWK. The function $f(\cdot)$ can be any KGE scoring function, such as the ones presented in Equations 1–3. RotatE and DistMult are particularly effective, and we use them in our experiments. We describe the details next.

RotatE (Complex Rotation). In RotatE, entities are embedded in a complex space $\mathbb{C}^{d/2}$, represented in practice by concatenating the real $\Re(\cdot)$ and imaginary $\Im(\cdot)$ parts in $\mathbb{R}^d$:

$$\mathbf{h}_h^{(L)} = [\Re(\mathbf{e}_h) \parallel \Im(\mathbf{e}_h)], \quad \mathbf{h}_t^{(L)} = [\Re(\mathbf{e}_t) \parallel \Im(\mathbf{e}_t)].$$

Each relation is parameterized by a phase vector $\boldsymbol{\theta}_r \in [-\pi, \pi]^{d/2}$, with complex embedding $\mathbf{r}^{\text{Rot}} = \cos \boldsymbol{\theta}_r + i \sin \boldsymbol{\theta}_r$. The relation acts as an element-wise rotation on the head embedding, and the score is

$$f_{\text{RotatE}}(h, r, t) = \gamma - \|\mathbf{e}_h \circ \mathbf{r}^{\text{Rot}} - \mathbf{e}_t\|_p, \quad (6)$$

where $\circ$ is element-wise complex multiplication, $\gamma > 0$ is a margin parameter, and $p \in \{1, 2\}$ controls the distance norm. This scorer is used with relation-agnostic GNNs (e.g., GraphSAGE), where the decoder plays an important role in adding relational semantics.

DistMult (Bilinear Dot Product). Using the relation embedding computed by DistMult $\mathbf{r}^{\text{DM}} \in \mathbb{R}^d$, the score is

$$f_{\text{DistMult}}(h, r, t) = \langle \mathbf{h}_h^{(L)} \circ \mathbf{r}^{\text{DM}}, \mathbf{h}_t^{(L)} \rangle = \sum_{k=1}^d h_{h,k}^{(L)} r_k^{\text{DM}} h_{t,k}^{(L)}, \quad (7)$$

where $\circ$ is element-wise multiplication and $\langle \cdot, \cdot \rangle$ is the dot product. This scorer is used with relation-aware GNNs (e.g., R-GCN), where relational semantics are already captured in the GNN weights.

4.3 Mini-Batch Training

To recap, the trainable parameters in gHAWK are: (i) feature fusion MLP weights, (ii) message-passing weights, and (iii) task-specific decoder weights. Training in gHAWK uses mini-batches, with different specifics for node property prediction and link prediction.

Node Property Prediction. For node-property prediction, each mini-batch $\mathcal{B}$ contains a set of labeled target nodes. For each $i \in \mathcal{B}$, we sample up to F_1 1-hop neighbors (and, if a second GNN layer is used, up to F_2 2-hop neighbors) to construct a computation subgraph. F_1 and F_2 are tuned per dataset according to the degree distribution, with graphs with high node degrees (heavy-tailed

distribution) using higher values. The sampled neighbors provide context for message passing but do not incur a loss term.

Given a mini-batch $\mathcal{B}$ of labeled nodes and their final embeddings $\{\mathbf{h}_i^{(L)}\}_{i \in \mathcal{B}}$, the classification head (Equation 5) produces predicted class probabilities $\hat{\mathbf{y}}_i$. Let $y_{i,c} \in \{0, 1\}$ denote the one-hot ground-truth vector for node i . We use a mini-batch cross-entropy loss

$$\mathcal{L}_{\text{CE}}(\mathcal{B}) = -\frac{1}{|\mathcal{B}|} \sum_{i \in \mathcal{B}} \sum_{c=1}^C y_{i,c} \log \hat{y}_{i,c}, \quad (8)$$

where $\hat{y}_{i,c}$ is the c -th component of $\hat{\mathbf{y}}_i$. Gradients are back-propagated through the classification head, the GNN layers, and the fusion MLPs, but not into the Bloom, TransE, or domain-specific features.

Link prediction. For link prediction, each mini-batch $\mathcal{B}$ consists of positive triples (h, r, t) sampled from the training set. For every such triple, we generate K negative triples by corrupting either the head or the tail, i.e., replacing h with h^- or t with t^- .

Let $f(h, r, t)$ denote the triple scoring function chosen from, e.g., Equations 6 and 7. For each positive $(h, r, t) \in \mathcal{B}$ and its K negative corruptions $\{(h_j^-, r, t_j^-)\}_{j=1}^K$, we compute the scores

$$s^+ = f(h, r, t), \quad s_j^- = f(h_j^-, r, t_j^-) \quad \text{for } j = 1, \dots, K.$$

Each negative triple is assigned a weight w_j , and the scores are combined into a mini-batch link-prediction loss $\mathcal{L}_{\text{link}}(\mathcal{B})$ that encourages true triples to score higher than corrupted ones

$$\mathcal{L}_{\text{link}}(\mathcal{B}) = \frac{1}{B} \sum_{(h,r,t) \in \mathcal{B}} \sum_{j=1}^K w_j \max\{0, \gamma + s_j^- - s^+\}, \quad (9)$$

with margin $\gamma > 0$ (we use $\gamma = 1.0$ unless stated otherwise). There are several methods to generate negative triples and set the corresponding weights w_j . We discuss these methods in the next section.

4.4 Sampling Negative Triples

The objective in training link prediction models is to score true (positive) triples that exist in the KG higher than false (negative) triples that do not exist. Negative triples are generated by corrupting the head or the tail. It is possible to enumerate all corruptions of every training triple, but this is infeasible except for the smallest KGs, so training relies on *negative sampling*: we generate a small set of negative triples for each positive triple.

It is well known that using hard (i.e., non-obvious) negative triples yields higher accuracy and faster convergence for link prediction models [41]. For example, if the positive triple is *(Austin, Capital_Of, Texas)*, then *(Austin, Capital_Of, Oklahoma)* is a hard negative while *(Austin, Capital_Of, Mount Everest)* is an easy and uninformative negative that does not help training as much as the first one. gHAWK has three different methods for sampling negative triples with varying hardness, which we discuss next.

Filtered Random Negatives. For each positive triple (h, r, t) , we draw K replacement entities uniformly at random to corrupt the head or tail.¹ Any corruption that appears as a known triple in the training, validation, or test sets is discarded. This is known as *filtered* sampling in KGE benchmarks, since we filter out true triples from the negative sample. The negative sampling budget K

¹We typically split the K budget evenly between the head and tail, but this is tunable.

controls the tradeoff between computation and the strength of the gradient signal: a larger K exposes the model to a more diverse set of alternatives but increases computational cost. All samples are given a weight $w_j = 1/K$ in Equation 9.

Self-adversarial Weighting. Random sampling tends to produce many “obvious” non-answers, especially as the model improves. To focus learning on confusable entities, we weight the candidate negatives in proportion to the model’s current score, following the self-adversarial scheme of RotatE [41]. Intuitively, negatives that the model currently considers plausible (higher score) receive larger weights and thus impose stronger corrective pressure.

Let $\{(h_j^-, r, t_j^-)\}_{j=1}^K$ be the set of corrupted negative triples associated with a positive triple (h, r, t) , with current model scores $s_j = f(h_j^-, r, t_j^-)$. Each negative triple can have a corrupted head or a corrupted tail, but not both. For example, if the tail is corrupted then $h_j^- = h$ and t_j^- is a uniformly sampled replacement tail. We define the weights in Equation 9 using a softmax with temperature $\alpha > 0$:

$$w_j = \frac{e^{\alpha s_j}}{\sum_{j'=1}^K e^{\alpha s_{j'}}}.$$

A larger α concentrates the weight on the highest-scoring (hardest) negatives, while a smaller α approaches uniform weighting. In practice we compute w_j from the current mini-batch scores and stop gradients through w_j for stability.

TransE-Guided Negative Sampling. The self-adversarial weighting above changes the weights of the candidate negatives, but these candidate negatives are still generated using uniform random sampling. A distinctive feature of gHAWK is that we train a TransE model during preprocessing, and this model is available for free when we sample negative triples. The TransE model provides a cheap, reasonably accurate measure of triple plausibility before GNN training. We exploit this by using TransE to propose hard negatives.

For each positive triple (h, r, t) , we first generate a large pool of K_{pool} candidate head and tail corruptions using filtered random sampling, with $K_{\text{pool}} \gg K$. We then score these candidates with the TransE scoring function $f_{\text{TransE}}(\cdot)$ and retain the top- K highest-scoring candidates as hard negatives. This TransE-guided ranking is computationally inexpensive since the TransE scoring function has few parameters, and it ensures that the GNN is exposed to informative, hard negatives even early in training. The K negatives are weighted using the self-adversarial scheme above, using the current gHAWK decoder scores $f(\cdot)$ in place of $f_{\text{TransE}}(\cdot)$.

5 COMPUTATION AND MEMORY REQUIRED

This section discusses the computational complexity and space requirement of gHAWK.

Preprocessing. We start with gHAWK’s preprocessing step, which has three components: constructing Bloom filters, training a TransE model, and feature fusion. The Bloom filters are constructed by Algorithm 1 in one pass over the triples, so this step’s time complexity is linear in the number of triples ($|\mathcal{T}|$) and the number of hash functions (k):

$$T_{\text{Bloom}} = O(k|\mathcal{T}|).$$

Each triple (h, r, t) is hashed twice per hash function, once for its head and once for its tail. This one-time cost is negligible compared to GNN training.

Bloom filters compactly encode neighborhoods as fixed-length bit vectors, ensuring a constant memory cost per node. The memory required for the Bloom filters is given by

$$M_{\text{Bloom}} = \frac{m}{8}|\mathcal{E}| \text{ bytes},$$

where m is the number of bits per Bloom filter. For instance, choosing $m = 1024$ results in a memory footprint of 1.28 GB for a graph with 10^7 entities, fitting within typical GPU memory.

The preprocessing step also trains a TransE model, with a time complexity of

$$T_{\text{TransE}} = O(|\mathcal{T}| d E_{\text{TransE}}),$$

where d is the TransE embedding dimensionality, and E_{TransE} is the number of epochs required for convergence. The memory required for storing these TransE embeddings is linear with respect to $|\mathcal{E}|$:

$$M_{\text{TransE}} = O(d|\mathcal{E}|) \text{ floats}.$$

Practically, even at $d = 200$, a graph with 10^7 nodes requires only around 8 GB, assuming 4 bytes per float.

The Bloom filter vectors and TransE embeddings are fused through a simple MLP projection. This fusion step is trivial compared to other preprocessing and training costs, with time complexity $O(|\mathcal{E}|)$.

Combining the previous equations, the total one-time preprocessing time complexity is made up of linear-time steps:

$$T_{\text{preprocessing}} = O(k|\mathcal{T}| + |\mathcal{T}| d E_{\text{TransE}} + |\mathcal{E}|),$$

while total preprocessing memory is:

$$M_{\text{preprocessing}} = O\left(\frac{m}{8}|\mathcal{E}| + d|\mathcal{E}|\right).$$

GNN Parameter Footprint. While gHAWK uses standard GNN backbones and does not add GNN parameters beyond the node features, it is still important to discuss the parameter footprint of different GNN methods, since these parameters dominate the memory consumption in the gHAWK pipeline.

As mentioned in Section 4.1, a GNN can be relation-aware or relation-agnostic. A relation-aware GNN like R-GCN [37] assigns separate parameters (i.e., a separate weight matrix) to each relation type. Specifically, each layer ℓ in an R-GCN model requires:

$$P_{\text{Rel-aware}}^{(\ell)} = d_{\text{hid}}^2 + |\mathcal{R}| \cdot d_{\text{hid}}^2,$$

where d_{hid} is the dimensionality of the hidden representation (embedding) and $|\mathcal{R}|$ is the number of relation types. The term d_{hid}^2 is the self-loop weight that updates a node’s own embedding. The second term corresponds to $|\mathcal{R}|$ relation-specific $d_{\text{hid}} \times d_{\text{hid}}$ weight matrices. This leads to a parameter complexity linear in the number of relation types ($|\mathcal{R}|$). Even techniques like basis or block decompositions [37] only reduce and do not eliminate this linear growth. As a result, relation-aware GNNs rapidly become infeasible as $|\mathcal{R}|$ grows (e.g., the OGB-WikiKG2 KG with 535 relation types).

In contrast, relation-agnostic GNNs like GraphSAGE [18] do not require separate weight matrices per relation type. Instead, they use a single weight matrix shared by all relations, along with a self-loop weight matrix:

$$P_{\text{Rel-agnostic}}^{(\ell)} = d_{\text{hid}}^2 + d_{\text{hid}}^2 = 2 \cdot d_{\text{hid}}^2,$$

where d_{hid} is the dimensionality of the hidden representation (embedding). The first d_{hid}^2 term represents the shared neighbor aggregation matrix. The second d_{hid}^2 term accounts for the self-loop weight matrix. Relation-agnostic GNNs dramatically reduce the number of parameters, since complexity no longer scales with $|\mathcal{R}|$. However, typical relation-agnostic methods sacrifice relational expressiveness because they ignore edge types. gHAWK can benefit both relation-aware and relation-agnostic methods, although it is expected to be of greater benefit to relation-agnostic methods, since it provides these methods with the semantic context that they lack.

GNN Training Epoch Complexity. The overall computational cost for a single GNN training epoch scales linearly with the number of batches N_{steps} , layers L , and per-batch edge computations $E(\mathcal{B})$:

$$T_{\text{epoch}} \approx N_{\text{steps}} L E(\mathcal{B}) d_{\text{hid}}.$$

In gHAWK, a shallow L (e.g., $L = 1$ or 2) is typically enough to achieve high accuracy.

6 EXPERIMENTS

6.1 Experimental Setup

gHAWK is implemented in Python and publicly available.² It uses PyTorch and the PyTorch Geometric library (PyG) [12]. Our experiments use datasets from the Open Graph Benchmark [20, 21].³ The datasets in this benchmark are already partitioned into training/validation/testing sets, and we adhere to this partitioning in our experiments. We use a single GPU server with AMD Genoa CPU, 768 GB of RAM, and 4 NVIDIA L40S GPUs, each with 48GB.

We use the AdamW optimizer for training. We tune the hyperparameters specifically for each experiment, adjusting the learning rate and weight decay through grid search or manual tuning. We use the mmh3 library [38] for the Bloom filters and tune the number of hash functions and bit length for each experiment. We measure training convergence by evaluating the model on the validation data after each epoch, or at specified intervals of epochs. Once training converges, we evaluate the learned model on the test data. Unless otherwise stated, we train with mini-batches of 1024 triples.

Our focus in this paper is on node property prediction and link prediction. Since these two tasks are very different in the datasets used, state-of-the-art baselines, and evaluation methodology, we present them independently in two separate sections: node property prediction in Section 6.2 and link prediction in Section 6.3. We evaluate model accuracy for node property prediction during validation and testing using multi-class classification accuracy, defined as the fraction of test nodes correctly labeled. For link prediction, we use filtered Mean Reciprocal Rate (MRR), Hits@3, and Hits@10.

6.2 Node Property Prediction

6.2.1 Task & Datasets. We evaluate node property prediction on two variants of the Microsoft Academic Graph (MAG) KG, which represents an academic bibliography containing information about publications, authors, venues, and subjects. Specifically, we use OGB-MAG [21] and MAG240M [20]. OGB-MAG contains ~ 1.9 M nodes (papers, authors, institutions, fields) and 4 edge types. The

task is to predict the venue (349 classes) for each paper. Each paper has a domain-specific feature vector that consists of a 128-dimensional Word2Vec [28] embedding of its title and abstract. MAG240M a web-scale bibliography graph, with ~ 244 M nodes and over 1.3B edges. The domain-specific feature vector of each paper is a 768-dimensional RoBERTa [27] embedding of the title and abstract concatenated together. The task is to predict one of 153 subject areas for 1.4M labeled arXiv papers. While both datasets represent academic bibliographies, we note the stark difference in scale between them: MAG240M has $126\times$ more nodes than OGB-MAG. Also, the RoBERTa features in MAG240M are more powerful and informative than the Word2Vec features in OGB-MAG. Since the Word2Vec and RoBERTa domain-specific features in this experiment rely on text, we refer to them as *text features*. The details of the two datasets are presented in Table 1.

Table 1: Node property prediction dataset statistics.

Statistic	OGB-MAG	MAG240M
Number of Entitie Types	4	3
Number of Relations	4	3
Total Nodes	1.94M	244M
Total Edges	21M	1.3B
Labeled Nodes	0.74M	1.4M
Feature Dimension	128 (Word2Vec)	768 (RoBERTa)

6.2.2 Baselines. We integrate gHAWK into several established GNN backbones that are widely used for node property prediction. We evaluate R-GCN [37], GraphSAGE [18], GraphSAINT [53], and ClusterGCN [8] to cover sampling-based and message-passing backbones at web scale. We additionally include GAT [46] and HGT [22] to represent attention-based and heterogeneous-attention models. These backbones span a range of architectural paradigms: R-GCN uses relation-specific parameters to model heterogeneous edges, GraphSAGE aggregates neighborhood features via mean pooling, GraphSAINT and ClusterGCN use sampling strategies for scalable training, GAT applies learned attention across neighbors, and HGT uses type-aware attention over meta-relations.

All models are run with the same parameter configuration, so differences in performance can be attributed solely to the node features. Specifically, each model has two GNN layers with 256 hidden units, dropout 0.5, neighbor sampling with fanout 25 at hop 1 and fanout 20 at hop 2, and an AdamW optimizer with learning rate 10^{-3} . We train OGB-MAG for 500 epochs and MAG240M for 100 epochs.

6.2.3 Feature Configurations. There are three types of features available for each node in this experiment: (1) gHAWK’s Bloom filter, (2) gHAWK’s TransE embedding, and (3) the text features for paper nodes. We evaluate the possible combinations of features, ranked from least informative to most informative:

- **No features:** features removed from the nodes (OGB-MAG), or replaced by a vector of random values (MAG240M). Here, the predictions are made exclusively based on graph structure.
- **Local Structure (Bloom):** Bloom filters only.
- **Text:** dataset-provided text features (Word2Vec in OGB-MAG; RoBERTa in MAG240M).

²<https://github.com/lids-lab/gHAWK>

³<https://ogb.stanford.edu>

Table 2: Node property prediction accuracy (%) on OGB-MAG (349 venues) and MAG240M (153 subject areas).

Model	OGB-MAG		MAG240M	
	Text (Word2Vec)	gHAWK+Text (Bloom+TransE+Word2Vec)	Text (RoBERTa)	gHAWK+Text (Bloom+TransE+RoBERTa)
GraphSAINT	46.84	57.97	64.73	73.29
GraphSAGE	45.90	53.04	66.32	71.15
HGT	43.78	52.23	57.49	74.97
GAT	OOM	49.92	66.30	71.95
R-GCN	37.86	48.13	68.60	75.04
ClusterGCN	36.57	45.70	61.85	72.02

- **Local + Text:** Bloom filters combined with text features.
- **gHAWK:** The Bloom filter and TransE embeddings of gHAWK *without* the text features. This allows us to compare the information provided by gHAWK’s structural encoding alone with the information provided by the text features.
- **gHAWK + Text:** The Bloom filter and TransE embeddings of gHAWK combined with text features. We hypothesize that this is the most informative set of features.

Feature dimensionality. In OGB-MAG, the Text feature is the 128-d Word2Vec embedding of each paper. We set the Bloom filter length to 128 bits, and we use 100 dimensions for TransE. We fuse the features into a 256-d vector for **Local + Text**, and a 356-d vector for **gHAWK + Text**.

In MAG240M, the Text feature is the 768-d RoBERTa embedding of each paper. We give 63 bytes to the Bloom filter and 100 dimensions to TransE. To keep the first GNN layer compact, we project the 768-d Text vector through a single-layer MLP to 384 dimensions. We fuse the features into a 447-d vector for **Local + Text**, and a 547-d vector for **gHAWK + Text**. In the **No features** case, each node has a 128-d feature vector of random numbers.

The basic question in this experiment is whether gHAWK improves the accuracy and convergence for all GNN backbones. To answer this question, we compare the unmodified GNN backbone to the gHAWK-augmented backbone. In both cases, we use the dataset obtained from OGB, including its text features. That is, we compare **Text** and **gHAWK + Text** from the list above. We also measure the speed of convergence in this experiment.

To perform an ablation study, we compare *all* the feature combinations in the list above, which enables us to compare the informativeness of different feature types.

6.2.4 Overall Accuracy and Convergence. Table 2 shows the accuracy of all GNN backbones with and without gHAWK (i.e., **Text** and **gHAWK + Text** features). Across both datasets and all backbones, gHAWK consistently improves accuracy. On OGB-MAG, gHAWK improves accuracy by 7 to 11 percentage points. GAT runs out of memory in the **Text** case since the features do not fit in GPU memory. On MAG240M, gHAWK improves accuracy by 4.8 to 17.5 percentage points, with the largest improvement for HGT.

The best accuracy is obtained by gHAWK with GraphSAINT on OGB-MAG (57.97%) and by gHAWK with R-GCN on MAG240M (75.04%). *At the time of writing, these results rank first on the OGB leaderboards for these datasets.* While the main objective of our experiments is demonstrating that gHAWK can improve any GNN backbone rather than topping OGB leaderboards, it is still remarkable that gHAWK can top two leaderboards with a generic




Figure 4: Model convergence on MAG240M. The plots show validation error versus training time (hours) for each GNN backbone. Solid curves represent gHAWK+Text (Bloom+TransE+RoBERTa) and dotted curves represent Text (RoBERTa). X markers denote the final validation error, with the numeric label showing its value.

technique that does not use external data or ensembles (typical strategies for other leaderboard-topping techniques).

We now turn to running time and convergence. On the smaller OGB-MAG dataset, all runs finish within a few minutes, so we omit detailed timing. On MAG240M, we observe consistent end-to-end speedups when moving from **Text** to **gHAWK + Text**. Figure 4 plots validation error versus training time on MAG240M for different backbones. gHAWK always converges faster and to a lower validation error than the GNN using the RoBERTa text features alone. The structural signals from gHAWK provide a strong prior that improves training and accelerates convergence.

Because the RoBERTa features are projected to 384 dimensions before fusion, gHAWK also reduces the parameter count of the first GNN layer by about 9% across backbones (e.g., GAT 3.1 → 2.8M; GraphSAGE/GraphSAINT/ClusterGCN 4.9 → 4.4M; HGT 31.4 → 30.7M; R-GCN 34.2 → 30.1M), which matches the faster convergence in Figure 4.

6.2.5 Ablation Study. Table 3 expands Table 2 and shows all feature configurations. The main message from this table is that the Bloom filter, TransE embeddings, and text features all add value, and none of them on its own can provide maximum accuracy.

For both datasets, **No features** has low accuracy, less than 30%. This shows that mini-batch training on the graph structure alone loses too much information and cannot achieve good accuracy, even for relation-aware backbones, such as R-GCN, which take into consideration relation types in addition to the graph structure. Node features are important for accurate training.

On OGB-MAG, **Local Structure (Bloom)** with the Bloom filter alone outperforms **Text** on every backbone, indicating that the patterns of citation and authorship relations are more predictive of venue than the text of the title and abstract, especially since the text is represented using Word2Vec, which is a weak method. The **gHAWK** feature combination, which includes the Bloom filter and TransE embeddings but not the text features, gives substantially higher accuracy than **Local Structure (Bloom)** or **Text**. This shows that capturing the local and global structure together, even

Table 3: Ablation over feature configurations: node property prediction accuracy (%) on OGB-MAG and MAG240M. “Text” is Word2Vec on OGB-MAG and RoBERTa on MAG240M.

Model	OGB-MAG						MAG240M					
	No Feat.	Local (Bloom)	Text (W2V)	Local +Text	gHAWK (B+T)	gHAWK +Text	No Feat.	Local (Bloom)	Text (RoB)	Local +Text	gHAWK (B+T)	gHAWK +Text
GraphSAINT	27.41	48.57	46.84	50.81	54.55	57.97	27.34	60.90	64.73	68.30	60.34	73.29
GraphSAGE	26.14	47.42	45.90	49.53	50.69	53.04	23.82	52.88	66.32	68.76	61.52	71.15
HGT	25.65	44.14	43.78	44.12	48.94	52.23	28.45	49.81	57.49	63.28	57.55	74.97
GAT	24.12	32.83	OOM	OOM	45.34	49.92	26.15	54.31	66.30	70.07	62.15	71.95
R-GCN	23.37	42.88	37.86	44.47	43.71	48.13	21.66	49.32	68.60	69.99	59.23	75.04
ClusterGCN	22.12	39.01	36.57	41.49	43.89	45.70	25.19	54.71	61.85	57.26	59.82	72.02

without text features, is better than capturing local structure alone or using the text features alone. As we argue throughout this paper, if every node has a representation of the graph structure, training can compensate for the loss of information in mini-batch sampling. Finally, as expected, combining all features in **gHAWK + Text** gives the highest accuracy.

The results are somewhat different on MAG240M, since the text features use the RoBERTa embedding of the paper title and abstract, which is a better text embedding model than Word2Vec, albeit more expensive. For this dataset, **Local Structure (Bloom)** recovers roughly 90% of the accuracy of **Text**, despite using a fraction of the feature vector dimensionality, confirming that structural information alone is highly informative. The final column, **gHAWK + Text**, has substantially higher accuracy than any of the other columns, showing that for this difficult dataset, all features must be used in combination to achieve maximum accuracy.

In summary, gHAWK improves accuracy for all GNN backbones, and the local structure (Bloom filter) and global structure (TransE embedding) are both needed to substitute or complement the text features.

6.3 Link Prediction

6.3.1 Task and Datasets. We evaluate gHAWK on link prediction tasks using two complementary KG datasets: OGB-WikiKG2 and FB15k-237. OGB-WikiKG2 is a large-scale knowledge graph from the OGB benchmark, containing ~2.5M entities, 535 relation types, and ~17M training triples. We follow the OGB evaluation protocol and report filtered MRR, Hits@3, and Hits@10 using the official evaluator, with 1000 sampled negatives per query triple. FB15k-237 is a widely used benchmark derived from Freebase with ~14k entities and 237 relations; inverse edges are removed to avoid test leakage. It contains 272K training triples, which allows exhaustive evaluation by ranking each test triple against all entity corruptions.

We use OGB-WikiKG2 as our primary large-scale benchmark, focusing on scalability and the effect of gHAWK when training with mini-batch sampling. FB15k-237 is used as a controlled setting for the ablation study, since it allows full-batch training even for relation-aware GNNs such as R-GCN. Table 4 summarizes the statistics of both datasets.

6.3.2 Baselines. We compare gHAWK against three families of link prediction baselines.

Table 4: Dataset statistics for link prediction. OGB-WikiKG2 is used for scalability analysis due to its large size, whereas FB15k-237 serves as a controlled standard benchmark for the ablation study.

Statistic	OGB-WikiKG2	FB15k-237
Number of Entities	2,500,604	14,541
Number of Relations	535	237
Training Triples	17,137,181	272,115
Validation Triples	429,456	17,535
Test Triples	598,543	20,466
Avg. Node Degree	~13.7	~37.4
Negative Sampling	1,000 sampled negatives per triple	All entities ranked exhaustively
Evaluation Protocol	OGB standard (filtered)	Standard filtered ranking

Embedding-only baselines. We include TransE and RotatE as strong KGE methods that operate purely at the level of global entity and relation embeddings, with no GNN and no message passing. Following the OGB recommendations, we use 500-d real embeddings for TransE and 250-d complex embeddings for RotatE (equivalent to 500 real dimensions). Both models are trained with a margin loss, $\gamma = 30$, and self-adversarial negative sampling. These baselines establish a strong “global-only” reference that ignores explicit local neighborhood structure.

Specialized link predictors. For additional context, we also consider NBFNet [59], which performs pairwise subgraph extraction and GNN reasoning per query, and the path-search heuristic A*Net [58]. Both methods achieve good accuracy on small benchmarks but do not scale to graphs as large as OGB-WikiKG2; NBFNet runs out of memory in our experiments.

GNN baselines. We consider two message-passing backbones: GraphSAGE as an example of a powerful relation-agnostic model and R-GCN as an example of a powerful relation-aware model.

In GraphSAGE, each node has a learned embedding, which is updated by a two-layer mean aggregator [18] encoder trained in a mini-batch fashion using PyG’s LinkNeighborLoader. Links are scored with a translational decoder such as RotatE or DistMult (Section 4.2).

For R-GCN, we follow the standard two-layer architecture with relation-specific parameters [37]. The GNN is trained on OGB-WikiKG2 in the same manner as GraphSAGE. For the ablation study, we use full-batch training on FB15k-237 with 500-dimensional hidden layers and basis decomposition. FB15k-237 is the only dataset that is small enough to allow full-batch training, which we use to obtain a strong relation-aware baseline.

6.3.3 Results and Discussions. We test several variants of link prediction models on OGB-WikiKG2: (i) a decoder-only variant where a TransE or RotatE decoder is used for link prediction without GNN layers, (ii) specialized link-prediction neural networks, namely NBFNet and A*Net, and (iii) relation-aware and relation-agnostic GNNs, namely R-GCN and GraphSAGE, trained with mini-batch training. We use a RotatE decoder with R-GCN and a DistMult decoder with GraphSAGE, since these decoders gave us the best results. We use gHAWK with different models as needed. Table 5 reports filtered test performance on OGB-WikiKG2, grouped into “w/o gHAWK” and “with gHAWK” columns. All models use the OGB evaluator and the same evaluation protocol.

For decoder-only models, RotatE outperforms TransE, reaching an MRR of 43.42% (Hits@10 48.98%). These values are consistent with prior state-of-the-art results for RotatE on the OGB-WikiKG2 dataset. When we replace the RotatE entity embeddings with gHAWK’s Bloom+TransE encoder but keep the same RotatE decoder, test MRR increases to 68.02% (Hits@10 83.19%). This is an impressive gain in MRR of 25 percentage points, demonstrating that gHAWK’s structural features alone, even without GNN message passing, can substantially improve a strong KGE decoder.

The specialized link-prediction neural networks, NBFNet and A*Net, did not give good results in our experiments. These recent state-of-the-art models showed impressive link prediction performance on small KGs [58, 59]. However, they did not do well on the large OGB-WikiKG2 dataset. NBFNet ran out of memory, and A*Net’s accuracy with gHAWK was worse than without gHAWK. The superior without-gHAWK performance was an MRR of 67.67%, lower than even the decoder-only RotatE with gHAWK.

R-GCN is conceptually appealing as a relation-aware message-passing baseline, but in practice, it is highly memory-hungry. For example, consider the memory requirement of full-batch training on OGB-WikiKG2, even without gHAWK. A two-layer R-GCN with 500-dimensional hidden states and 535 relations (or 2×535 when adding inverse edges) requires hundreds of relation-specific weight matrices. The standard PyG RGCNConv layer materializes a parameter tensor of size $[\text{num_relations}, d, d]$, which scales as $O(|\mathcal{R}|d^2)$. On OGB-WikiKG2, with $|\mathcal{R}| = 535$ and d in the hundreds, this already occupies several gigabytes of GPU memory per layer. When we combine this with a large entity embedding table (millions of entities, hundreds of dimensions) and AdamW optimizer state, full-batch R-GCN consistently runs out of memory on our L40S GPU with 48GB of memory.

To obtain the R-GCN results shown in Table 5, we reduce the required memory by using a small batch size (400) and reduced projection dimensions (60), while keeping an RGCN-style relation-specific convolution layer. In this setting, a two-layer R-GCN trained with PyG’s RGCNConv and LinkNeighborLoader achieves 18.16% test MRR (25.44% Hits@10), while still using a significant fraction of

Table 5: Effect of gHAWK features on different backbones on OGB-WikiKG2. All numbers are filtered test MRR / Hits@3 / Hits@10 (%).

Method	w/o gHAWK			with gHAWK		
	MRR	H@3	H@10	MRR	H@3	H@10
TransE	35.88	37.04	41.97			
RotatE	43.42	44.10	48.98	68.02	72.11	83.19
NBFNet	OOM	OOM	OOM			
A*Net	67.67	-	-			
R-GCN	18.16	18.70	25.44	38.96	42.38	55.57
GraphSAGE	45.37	49.98	63.67	75.74	76.63	83.65

GPU memory. This weak performance highlights the information loss caused by neighborhood sampling and the difficulty of training heavily parameterized relation-aware GNN layers at this scale. R-GCN with gHAWK achieves 38.96% MRR (55.57% Hits@10), much better than R-GCN without gHAWK, but still far from the best performance, even lower than the decoder-only RotatE.

The GraphSAGE backbone follows the same pattern. Without gHAWK, a two-layer GraphSAGE encoder with a DistMult decoder reaches a good test MRR of 45.37% (Hits@10 63.67%), despite being relation-agnostic in its message passing. A subtle point in our setup is that GraphSAGE by itself is not a link prediction model for multi-relational graphs: its message passing is completely relation-agnostic. The model becomes relation-aware only once we attach the DistMult decoder on top of the node embeddings (Section 4.2). Consequently, the good performance reported for the GraphSAGE in Table 5 should be understood as the combination of the GraphSAGE relation-agnostic encoder with the DistMult decoder that models relation types in its scoring function, thereby injecting some relation-awareness into the model. In preliminary experiments (not shown), replacing DistMult with a relation-agnostic dot-product scorer significantly degraded MRR, confirming the need for relation-awareness in the decoder. When we augment this backbone with gHAWK features, test MRR increases to 75.74% (Hits@10 83.65%). **At the time of writing, this MRR ranks first on the OGB-WikiKG2 leaderboard.** As we commented in the node property classification section, our main objective is not topping leaderboards, but it is still remarkable that gHAWK can top leaderboards in both node property prediction and link prediction.

It is interesting that, while gHAWK benefits the relation-aware R-GCN, the best performance is obtained with the relation-agnostic GraphSAGE, demonstrating that gHAWK effectively captures strong training signals about the graph structure and relation types in its node features and decoder. We empirically observe that once nodes are initialized with these features, shallow message passing in a relation-agnostic model is sufficient to obtain strong link prediction performance, and a relation-aware model with heavy relation-specific parameterization is not required.

Each node starts with a representation that already encodes both its typed 1-hop neighborhood (via the Bloom filter) and its global position in the KG (via the TransE embedding). In this setting, the GraphSAGE layers act primarily as a refinement mechanism rather than the sole source of structural information. Across our

experiments, one or two GraphSAGE layers consistently yield the best performance. More layers either plateau or slightly degrade MRR while incurring additional computation and memory cost. With gHAWK, the “heavy lifting” is done before message passing, and shallow propagation is enough to align and denoise the node representations.

We also examine the speed of convergence for gHAWK models on the link prediction task. On OGB-WikiKG2, almost all of the MRR gain provided by gHAWK on RotatE, R-GCN, and GraphSAGE appears within the first 10–20 epochs. After this point, the validation curves flatten, and subsequent epochs primarily fine-tune the scores rather than substantially change the ranking. This behavior is consistent with our previous observation: the Bloom+TransE features provide a prior that already encodes most of the useful local and global structure, and a small number of message-passing steps is enough to propagate and smooth these priors.

In summary, gHAWK consistently improves the link prediction performance of both pure KGE baselines (RotatE) and message-passing baselines (R-GCN, GraphSAGE). It requires shallow message passing and converges in a few epochs, thereby successfully scaling GNN training on large heterogeneous KGs such as OGB-WikiKG2.

6.3.4 Ablation Study. To understand the contributions of gHAWK’s Bloom filters and TransE embeddings, we perform controlled ablations on the FB15k-237 dataset by incrementally adding the two types of features to a mini-batch R-GCN baseline. We also evaluate full-batch training on this dataset to assess the accuracy loss due to sampling for mini-batch formation. Table 6 shows the ablation results. All model variants in the table share the same R-GCN architecture, optimizer, number of training epochs, and hyperparameters. We vary only the node input features (Bloom only, TransE only, or Bloom+TransE), ensuring that differences in performance can be attributed directly to these features.

Table 6: Performance of various R-GCN models with gHAWK variants on FB15k-237. MRR / Hits@3 / Hits@10 in %.

Model Variant	MRR	Hits@3	Hits@10	Notes
Full-batch	22.87	25.15	41.50	Baseline
Mini-batch	14.86	15.09	26.00	Neighbor sampling
Bloom	26.39	28.98	44.44	Local structure
TransE	22.18	24.07	39.39	Global structure
Bloom + TransE	27.95	30.39	44.82	gHAWK

The FB15k-237 dataset is challenging for link prediction, despite its small size. The first row of Table 6 shows full-batch training of the R-GCN. The second row of the table shows mini-batch training based on neighborhood sampling. The information loss due to sampling reduces MRR from 22.87% to 14.86%. Adding a Bloom filter to each node yields a dramatic improvement: MRR jumps to 26.39%, surpassing even the performance of full-batch R-GCN. This result confirms that the explicit neighborhood summaries provided by the Bloom filters can compensate for the information loss due to sampling. Adding TransE embeddings alone (without Bloom filters) also helps, but to a lesser extent: MRR improves to 22.18%, just approaching the full-batch MRR. The TransE embeddings summarize global structure and provide the semantic context of each

node, which aids learning, but they cannot fully compensate for missing information about local structure. Combining both Bloom and TransE features with mini-batch training yields the best results: 27.95% MRR (44.82% Hits@10). gHAWK features restore the performance lost by neighbor sampling and even surpass the accuracy of full-batch training. These results validate gHAWK’s robustness, generality, and ability to mitigate performance degradation from mini-batch sampling.

7 RELATED WORK

Graph Representation Learning. This paper builds on a large body of work on graph representation learning. The simplest graph representation methods are KGE methods, which treat the graph as a collection of triples and ignore complex structural patterns. TransE [6] models relations as translations and learns in linear time, but struggles with symmetric and one-to-many relations. RotatE [41] handles symmetric and inverse relations by relying on rotations on complex numbers. DistMult [51] uses a diagonal bilinear scoring function, making it efficient but limited to symmetric relations, while ComplEx [44] extends DistMult to the complex numbers domain, capturing asymmetric and anti-symmetric relations. These models capture the global semantic context of a graph in constant time per triple, but they lack explicit signals about the local neighborhood of each node. gHAWK uses TransE to encode global structure, a choice discussed extensively in Section 3.2.

KGE training is efficient and parallelizable [25], so creating a TransE model is not a bottleneck in gHAWK. The performance of KGE models on the important database problem of entity-alignment has been benchmarked [42], showing that TransE outperforms more complex models on most datasets. Beyond improving the scoring of triples, recent work on KGEs emphasizes explainability for embedding-based link prediction: Kelpie [36] attributes predictions to training facts, and eXPath [40] derives ontology-aware closed-path rules as human-readable explanations. Explainability is not a focus of gHAWK, but using these works to explain gHAWK predictions is an interesting direction for future work.

GNNs are the more recent and accurate class of graph representation methods. Many message-passing GNN architectures have been proposed in recent years. GraphSAGE [18] is a prominent and popular example of GNNs for homogeneous graphs. For KGs, which are the focus of this paper, several relation-aware techniques have been proposed, such as R-GCN [37], which assigns a distinct weight matrix to every relation and therefore has a memory requirement that grows quadratically with the hidden dimension and linearly with the number of relations. Later variants include CompGCN [45], which introduces compositional operators, and HGT [22], which adopts relation-aware self-attention. These methods still multiply the parameters by the number of relations, limiting their practicality on large KGs, especially those with many relations. The structure awareness provided by gHAWK can improve the scalability of any GNN method, and is of particular benefit to relation-agnostic GNNs.

Scalable GNN Training. GNN training involves each node aggregating information from its neighbors. The ideal approach to maximize accuracy is to use full-batch training, where all nodes and their neighbors are processed in each training epoch. However, the computational and memory requirements of full-batch training

rapidly escalate, a phenomenon known as “neighborhood explosion.” To address this scalability issue, researchers have developed training techniques that limit neighbor aggregation. Sampling-based methods like GraphSAGE [18] sample a fixed number of neighbors per node and ignore the rest. NodePiece [14] represents every node by a short list of anchors (well-chosen reference nodes) and looks up their IDs in a compact embedding table, shrinking the total parameter size. Graph partitioning approaches like FastGCN [7], Cluster-GCN [8], and GraphSAINT [53] operate on smaller sub-graphs or clusters, so each node perceives a reduced neighborhood. These methods process only portions of the graph at each training step, which improves scalability. However, they exclude potentially important structural information outside the processed nodes, which inevitably degrades accuracy. The Bloom filter neighborhood summary in gHAWK can restore some of the lost accuracy by including a representation of the neighborhood in each node.

Another significant scalability challenge arises from the high heterogeneity of many real-world KGs, which typically contain highly diverse entity types (e.g., people, places, organizations) and various relation types (e.g., bornIn, locatedIn, familyOf), each with unique semantics. For example, the Freebase [5, 32] KG contains approximately 125 million triples across thousands of distinct relations. Handling such diversity often necessitates having a different set of GNN parameters per relation or using specialized architectures [13, 37, 45]. Naively assigning separate parameters for each relation leads to parameter explosion [49]. Hence, scalable KG models must effectively share parameters among relations or employ other strategies to manage heterogeneity efficiently. The TransE embeddings of gHAWK can provide information about the various relations to GNN techniques that share parameters among relations, improving accuracy and convergence.

End-to-end graph learning systems must also deal with scalability challenges. AliGraph [57] co-designs storage, neighbor sampling, and execution to keep training feasible at scale. Decoupled GNNs [56] reduce propagation cost on evolving graphs. EC-Graph [39] reduces distributed overhead via error-compensated communication, highlighting the importance of system choices for GNN training. gHAWK can be incorporated into any of these systems.

Specialized GNNs for Link Prediction. Recent work has focused on developing specialized GNNs (structural encoders) for link prediction, such as SEAL [54] and NBFNet [59]. These GNNs extract a local subgraph around each candidate pair (h, t) and run a GNN on it, incurring *pairwise* cost, with both memory and computation growing linearly with the number of *pairs*. We show in our experiments that NBFNet runs out of memory on the large OGB-WikiKG2 KG. Furthermore, enumerating the pairwise sub-graphs can become a bottleneck, and recent work has aimed to mitigate this bottleneck. HUGE [52] develops an efficient engine for subgraph enumeration, while TIGER [48] accelerates inductive reasoning subgraph extraction for KG-centered GNNs. gHAWK does not extract pairwise, so it is not affected by this bottleneck.

Node Features. Adding node features to improve GNN training is common practice. For example, it is possible to include in each node a random-walk embedding of this node [16, 33], and OGB recommends this approach to add features to the MAG240M nodes that do not have features (recall that MAG240M provides features only

for paper nodes). Bloom-signature GNNs [55] hash neighborhoods in homogeneous graphs. The innovation in gHAWK is developing an approach that combines local and global structure encoding, works for heterogeneous graphs, and avoids the sampling bias of the underlying GNN.

8 CONCLUSION

Training GNNs on large, heterogeneous KGs remains challenging: GNNs learn global and local structure only through message passing, which is computationally expensive. Relation-aware GNNs that maintain per-relation neural network parameters do not work for KGs with a large number of relations, while relation-agnostic GNNs discard all information about relation types. gHAWK adopts a novel approach to address these problems and *pre-loads* each node with a feature vector that encodes the local and global graph structure. gHAWK uses a Bloom filter to represent the local neighborhood structure and TransE embeddings to represent the global KG structure and the semantic context of each node.

The gHAWK feature vectors enable the use of relation-agnostic GNNs for large KGs while preserving information about relations and thus maintaining accuracy. In addition, gHAWK can attach a relation-sensitive decoder as the final stage of the GNN, enabling accurate link prediction, even for relation-agnostic GNNs. gHAWK also benefits relation-aware GNNs, although these GNNs are not scalable for KGs with many relations. gHAWK allows GNNs to provide accurate predictions with shallow (1–2 layer) neural networks. Our experiments show that gHAWK improves accuracy, memory requirement, and training time for node property prediction and link prediction, representing a major step toward graph representation learning for web-scale heterogeneous KGs, and showing that learning at this scale requires injecting compact, approximate structural priors.

REFERENCES

- [1] Hussein Abdallah, Waleed Afandi, Panos Kalnis, and Essam Mansour. 2024. Task-Oriented GNNs Training on Large Knowledge Graphs for Accurate and Efficient Modeling. In *ICDE*. 1833–1846.
- [2] Farahnaz Akrami, Mohammed Samiul Saeef, Qingheng Zhang, Wei Hu, and Chengkai Li. 2020. Realistic re-evaluation of knowledge graph completion methods: An experimental study. In *SIGMOD*. 1995–2010.
- [3] Lei Jimmy Ba, Jamie Ryan Kiros, and Geoffrey E. Hinton. 2016. Layer Normalization. *arXiv preprint arXiv:1607.06450* (2016).
- [4] Burton H Bloom. 1970. Space/time trade-offs in hash coding with allowable errors. *Commun. ACM* 13, 7 (1970), 422–426.
- [5] Kurt Bollacker, Colin Evans, Praveen Paritosh, Tim Sturge, and Jamie Taylor. 2008. Freebase: A collaboratively created graph database for structuring human knowledge. In *SIGMOD*. 1247–1250.
- [6] Antoine Bordes, Nicolas Usunier, Alberto Garcia-Duran, Jason Weston, and Oksana Yakhnenko. 2013. Translating Embeddings for Modeling Multi-Relational Data. *NeurIPS* 26 (2013).
- [7] Jie Chen, Tengfei Ma, and Cao Xiao. 2018. Fastgcn: fast learning with graph convolutional networks via importance sampling. In *ICLR*.
- [8] Wei-Lin Chiang, Xuanqing Liu, Si Si, Yang Li, Samy Bengio, and Cho-Jui Hsieh. 2019. Cluster-gcn: An efficient algorithm for training deep and large graph convolutional networks. In *KDD*. 257–266.
- [9] Francesco Di Giovanni, Lorenzo Giusti, Federico Barbero, Giulia Luise, Pietro Lio, and Michael M Bronstein. 2023. On over-squashing in message passing neural networks: The impact of width, depth, and topology. In *International conference on machine learning*. PMLR, 7865–7885.
- [10] Laura Dietz, Alexander Kotov, and Edgar Meij. 2018. Utilizing knowledge graphs for text-centric information retrieval. In *ACM SIGIR Conf. on Research & Development in inf. Retrieval*. 1387–1390.
- [11] Kien Do, Truyen Tran, and Svetha Venkatesh. 2018. Knowledge graph embedding with multiple relation projections. In *Int. Conf. on Pattern Recognition (ICPR)*. 332–337.

- [12] Matthias Fey and Jan Eric Lenssen. 2019. Fast Graph Representation Learning with PyTorch Geometric. *arXiv preprint arXiv:1903.02428* (2019).
- [13] Xinyu Fu, Jiani Zhang, Ziqiao Meng, and Irwin King. 2020. MAGNN: Metapath aggregated graph neural network for heterogeneous graph embedding. In *Proc. of the Web Conf.* 2331–2341.
- [14] Mikhail Galkin, Etienne Denis, Jiapeng Wu, and William L Hamilton. 2022. Node-piece: Compositional and parameter-efficient representations of large knowledge graphs. In *ICLR*.
- [15] Xiou Ge, Yun Cheng Wang, Bin Wang, C-C Jay Kuo, et al. 2024. Knowledge graph embedding: An overview. *APSIPA Transactions on Signal and Information Processing* 13, 1 (2024).
- [16] Aditya Grover and Jure Leskovec. 2016. node2vec: Scalable feature learning for networks. In *KDD*. 855–864.
- [17] Qingyu Guo, Fuzhen Zhuang, Chuan Qin, Hengshu Zhu, Xing Xie, Hui Xiong, and Qing He. 2022. A Survey on Knowledge Graph-based Recommender Systems. *IEEE Trans. Knowl. Data Eng.* 34, 8 (2022), 3549–3568.
- [18] Will Hamilton, Zitao Ying, and Jure Leskovec. 2017. Inductive representation learning on large graphs. *NeurIPS* 30 (2017).
- [19] Aidan Hogan, Eva Blomqvist, Michael Cochez, Claudia d’Amato, Gerard De Melo, Claudio Gutierrez, Sabrina Kirrane, José Emilio Labra Gayo, Roberto Navigli, Sebastian Neumaier, et al. 2021. Knowledge Graphs. *Comput. Surveys* 54, 4 (2021), 1–37.
- [20] Weihua Hu, Matthias Fey, Hongyu Ren, Maho Nakata, Yuxiao Dong, and Jure Leskovec. 2021. OGB-LSC: A large-scale challenge for machine learning on graphs. In *NeurIPS*. *arXiv preprint arXiv:2103.09430*.
- [21] Weihua Hu, Matthias Fey, Marinka Zitnik, Yuxiao Dong, Hongyu Ren, Bowen Liu, Michele Catasta, and Jure Leskovec. 2020. Open graph benchmark: Datasets for machine learning on graphs. *NeurIPS* 33 (2020), 22118–22133.
- [22] Ziniu Hu, Yuxiao Dong, Kuansan Wang, and Yizhou Sun. 2020. Heterogeneous graph transformer. In *Proc. of the Web Conf.* 2704–2710.
- [23] Nandish Jayaram, Arijit Khan, Chengkai Li, Xifeng Yan, and Ramez Elmasri. 2015. Querying Knowledge Graphs by Example Entity Tuples. *IEEE Trans. Knowl. Data Eng.* 27, 10 (2015), 2797–2811.
- [24] Zhuoran Jin, Pengfei Cao, Yubo Chen, Kang Liu, and Jun Zhao. 2022. A good neighbor. A found treasure: Mining treasured neighbors for knowledge graph entity typing. In *EMNLP*. 480–490.
- [25] Adrian Kochsiek and Rainer Gemulla. 2021. Parallel training of knowledge graph embedding models: a comparison of techniques. *PVLDB* 15, 3 (2021), 633–645.
- [26] Xi Victoria Lin, Richard Socher, and Caiming Xiong. 2018. Multi-Hop Knowledge Graph Reasoning with Reward Shaping. In *EMNLP*. 3243–3253.
- [27] Yinhan Liu, Myle Ott, Naman Goyal, Jingfei Du, Mandar Joshi, Danqi Chen, Omer Levy, Mike Lewis, Luke Zettlemoyer, and Veselin Stoyanov. 2019. Roberta: A robustly optimized bert pretraining approach. *arXiv preprint arXiv:1907.11692* (2019).
- [28] Tomas Mikolov, Kai Chen, Greg Corrado, and Jeffrey Dean. 2013. Efficient estimation of word representations in vector space. *arXiv preprint arXiv:1301.3781* (2013).
- [29] Belinda Mo, Kyssen Yu, Joshua Kazdan, Proud Mpala, Lisa Yu, Chris Cundy, Charilaos Kanatsoulis, and Sanmi Koyejo. 2025. KGGen: Extracting Knowledge Graphs from Plain Text with Language Models. *arXiv preprint arXiv:2502.09956* (2025).
- [30] Aisha Mohamed, Shameem Puthiya Parambath, Zoi Kaoudi, and Ashraf Aboul-naga. 2020. Popularity Agnostic Evaluation of Knowledge Graph Embeddings. In *Proc. Conf. on Uncertainty in Artificial Intelligence (UAI)*. 1059–1068.
- [31] Maximilian Nickel, Kevin Murphy, Volker Tresp, and Evgeniy Gabrilovich. 2015. A Review of Relational Machine Learning for Knowledge Graphs. *Proc. IEEE* 104, 1 (2015), 11–33.
- [32] Thomas Pellissier Tanon, Denny Vrandečić, Sebastian Schaffert, Thomas Steiner, and Lydia Pintscher. 2016. From freebase to wikidata: The great migration. In *WWW*. 1419–1428.
- [33] Bryan Perozzi, Rami Al-Rfou, and Steven Skiena. 2014. Deepwalk: Online learning of social representations. In *KDD*. 701–710.
- [34] Simon Razniewski, Hiba Arnaout, Shrestha Ghosh, and Fabian Suchanek. 2024. Completeness, recall, and negation in open-world knowledge bases: A survey. *Comput. Surveys* 56, 6 (2024), 1–42.
- [35] Joshua Robinson, Rishabh Ranjan, Weihua Hu, Xexin Huang, Jiaqi Han, Alejandro Dobles, Matthias Fey, Jan Eric Lenssen, Yiwen Yuan, Zecheng Zhang, Xinwei He, and Jure Leskovec. 2024. RelBench: A Benchmark for Deep Learning on Relational Databases. In *Proc. Conf. on Neural Information Processing Systems (NeurIPS)*.
- [36] Andrea Rossi, Donatella Firmani, Paolo Merialdo, and Tommaso Teofili. 2022. Explaining link prediction systems based on knowledge graph embeddings. In *SIGMOD*. 2062–2075.
- [37] Michael Schlichtkrull, Thomas N Kipf, Peter Bloem, Rianne Van Den Berg, Ivan Titov, and Max Welling. 2018. Modeling relational data with graph convolutional networks. In *The Semantic Web: Int. Conf. ESWC*. 593–607.
- [38] Hajime Senuma. 2025. MMH3: A Python extension for MurmurHash3. *Journal of Open Source Software* 10, 105 (2025), 6124.
- [39] Zhen Song, Yu Gu, Jianzhong Qi, Zhigang Wang, and Ge Yu. 2022. EC-Graph: A distributed graph neural network system with error-compensated compression. In *ICDE*. 648–660.
- [40] Ye Sun, Lei Shi, and Yongxin Tong. 2024. eXpath: Explaining Knowledge Graph Link Prediction with Ontological Closed Path Rules. *arXiv preprint arXiv:2412.04846* (2024).
- [41] Zhiqing Sun, Zhi-Hong Deng, Jian-Yun Nie, and Jian Tang. 2019. Rotate: Knowledge graph embedding by relational rotation in complex space. In *ICLR*.
- [42] Zequn Sun, Qingheng Zhang, Wei Hu, Chengming Wang, Muhao Chen, Farahnaz Akrami, and Chengkai Li. 2020. A Benchmarking Study of Embedding-based Entity Alignment for Knowledge Graphs. *PVLDB* 13, 11 (2020).
- [43] Thiviyana Thanapalasingam, Lucas van Berkel, Peter Bloem, and Paul Groth. 2022. Relational graph convolutional networks: A closer look. *PeerJ Computer Science* 8 (2022), e1073.
- [44] Théo Trouillon, Johannes Welbl, Sebastian Riedel, Éric Gaussier, and Guillaume Bouchard. 2016. Complex embeddings for simple link prediction. In *Int. Conf. on Machine Learning*. 2071–2080.
- [45] Shikhar Vashishth, Soumya Sanyal, Vikram Nitin, and Partha Talukdar. 2019. Composition-based multi-relational graph convolutional networks. In *ICLR*.
- [46] Petar Velickovic, Guillem Cucurull, Arantxa Casanova, Adriana Romero, Pietro Lio, Yoshua Bengio, et al. 2016. Graph attention networks. In *ICLR*.
- [47] Denny Vrandečić and Markus Krötzsch. 2014. Wikidata: a free collaborative knowledgebase. *Commun. ACM* 57, 10 (2014), 78–85.
- [48] Kai Wang, Yuwei Xu, and Siqiang Luo. 2024. Tiger: Training inductive graph neural network for large-scale knowledge graph reasoning. *PVLDB* 17, 10 (2024), 2459–2472.
- [49] Quan Wang, Zhendong Mao, Bin Wang, and Li Guo. 2017. Knowledge graph embedding: A survey of approaches and applications. *IEEE Trans. Knowl. Data Eng.* 29, 12 (2017), 2724–2743.
- [50] Chenyan Xiong, Russell Power, and Jamie Callan. 2017. Explicit Semantic Ranking for Academic Search via Knowledge Graph Embedding. In *Proc. Int. Conf. on World Wide Web (WWW)*. 1271–1279.
- [51] Bishan Yang, Wen-tau Yih, Xiaodong He, Jianfeng Gao, and Li Deng. 2015. Embedding entities and relations for learning and inference in knowledge bases. In *ICLR*.
- [52] Zhengyi Yang, Longbin Lai, Xuemin Lin, Kongzhang Hao, and Wenjie Zhang. 2021. Huge: An efficient and scalable subgraph enumeration system. In *SIGMOD*. 2049–2062.
- [53] Hanqing Zeng, Hongkuan Zhou, Ajitesh Srivastava, Rajgopal Kannan, and Viktor Prasanna. 2019. Graphsaint: Graph sampling based inductive learning method. In *ICLR*.
- [54] Muhao Zhang and Yixin Chen. 2018. Link Prediction Based on Graph Neural Networks. In *NeurIPS*.
- [55] Tianyi Zhang, Haoteng Yin, Rongzhe Wei, Pan Li, and Anshumali Shrivastava. 2024. Learning Scalable Structural Representations for Link Prediction with Bloom Signatures. In *Proceedings of the ACM Web Conference 2024*. 980–991.
- [56] Xiangrong Zheng et al. 2023. Decoupled Graph Neural Networks for Large Dynamic Graphs. *PVLDB* 16, 10 (2023), 2239–2247.
- [57] Rong Zhu, Kun Zhao, Hongxia Yang, Wei Lin, Chang Zhou, Baole Ai, Yong Li, and Jingren Zhou. 2019. Aligraph: A comprehensive graph neural network platform. *PVLDB* 12, 12 (2019), 2094–2105.
- [58] Zhaocheng Zhu, Xinyu Yuan, Michael Galkin, Louis-Pascal Xhonneux, Ming Zhang, Maxime Gazeau, and Jian Tang. 2023. A* net: A scalable path-based reasoning approach for knowledge graphs. *Advances in Neural Information Processing Systems* 36 (2023), 59323–59336.
- [59] Zhaocheng Zhu, Zuobai Zhang, Louis-Pascal Xhonneux, and Jian Tang. 2021. Neural bellman-ford networks: A general graph neural network framework for link prediction. *NeurIPS* 34 (2021), 29476–29490.